

## POWER PACKS



### HYDRAULIC CHARACTERISTICS

MODEL	PUMP CODE	FLOW RATE AT 1450 RPM	ELECTRIC									TANK kg	
			0.5 HP	0.75 HP	1 HP	1.5 HP	2 HP	3 HP	5 HP	7.5 HP	10 HP	CAPACITY	
EH -20-G-1.2-X	3003	1.2	130										20
EH -20-G-1.8-X	3004	1.8	100	130	170								20
EH -20-G-2.5-X	3006	2.5	60	90	125								20
EH -20-G-3.4-X	3008	3.4		70	90	138							20
EH 30-G-4.8-X	3011	4.8		50	65	95	130						30
EH 30-G-5.8-X	3013	5.8		40	55	80	110	160					30
EH 40-G-6.8-X	3015	6.8			45	70	90	140					40
EH 40-G-7.7-X	3017	7.7			40	60	80	120	200				40
EH -50-G-9.1-X	3020	9.1			35	50	70	100	170				50
EH -80-G-12.7-X	3028	12.7				35	50	75	120	180			80
EH -80-G-16.4-X	3036	16.4				30	38	57	95	140	190		80
EH -100-G-20-X	3044	20					30	45	80	120	155		100
EH -100-G-23.6-X	3052	23.6						40	65	100	130		100
EH -150-G-27.3-X	3060	27.3						35	55	85	115		150
EH -150-G-32.7-X	3072	32.7							45	70	95		150
EH -200-G-41-X	3090	41							38	57	75		200
EH -200-G-47.7-X	3150	47.7							30	50	65		200
EH -275-G-54.5-X	3120	54.5								40	55		275
EH -275-G-66.5-X	3146	66.5								35	45		275
EH -350-G-71.8-X	3158	71.8									40		350
EH -500-G-100-X	3220	100									30		500